

EnTech Industries

1109 10th Street NE, East Grand Forks, MN 56721
Phone: (218)773-6602 Fax: (218)773-6607

1038 North Cedar Street, New Castle, PA 16102
Phone: (724)202-6740 Fax: (724)202-6794



2 DC CYCLONE

Options

Electric Powered

15 HP 230 or 480 VAC 3 PH

Filter

Standard Qx Media 80/20 Blend

SB (Spun Bonded Polyester) MERV 12 initial rating

SBTX (HEPA Equivalent)

HEPA Secondary Final Filter

Filter Restriction Warning Light

Pulse System

Direct Pilot Valves

Onboard Air Compressor

Waste Removal

Gravity Dump

Electric Powered Auger

Hydraulic Powered Auger

Vibrator – Air Powered

Vibrator – Electric Powered

Frame Configuration

Skid With Gravity Dump

Skid With Auger Discharge

Trailer With Auger Discharge

Crane Pick Points

Fork Lift Pockets

Storage Storage Boxes

Jack Heavy Duty Jack

Fuel

Large Fuel Fill

Grease Gun

Tie Down Points

Dryer

Air Dryer

Paint

Custom Company Color

Standard Features

Filtration 4 top loading cartridges

Filter Cleaning Timed cycle reverse air pulse

Air Inlets Two 6" inlet ports

Air to Cloth Ratio 1.92:1 at 2,000 cfm

Filter Media 1,040 sq. ft. moisture resistant cellulose resin material (standard)

Efficiency 99.8% at 0.5 micron particle after initial dust load
MERV 12 initial rating

Material Discharge Hydraulic powered auger

Dimensions 86"H x 40"W x 96"L

Engine Diesel Tier 4 Compliant

Fan Non-Overloading, Spark Resisting

Air Flow Rates 2,000 cfm @ 12" w.c.

Fuel Consumption 1 Gallon per hour

Fuel Storage 18 gallons

Electrical System 12V dc

Weight 2,800 lbs. actual

Skid mount with Fork Lift pockets

Paint ETI Gray

Warranty One Year or 1500 hours

Whichever occurs first limited