

ETI[®]

EnTech Industries

1109 10th Street NE, East Grand Forks, MN 56721
Phone: (218)773-6602 Fax: (218)773-6607

1038 North Cedar Street, New Castle, PA 16102
Phone: (724)202-6740 Fax: (724)202-6794

60 DC CYCLONE



Standard Features

Filtration 75 top loading cartridges
Filter Cleaning Timed cycle reverse air pulse
Air Inlets Eight 20" inlet ports, minimum three in use
Air to Cloth Ratio 2.56:1 at 60,000 cfm
Filter Media 23,400 sq. ft. moisture resistant cellulose resin material (standard)
Efficiency 99.8% at 0.5 micron particle after initial dust load
MERV 12 initial rating
Material Discharge Hydraulic powered auger
Dimensions 142"H x 102"W x 612"L
Engine John Deere 6068 = 6.8L
Fan Non-Overloading, Spark Resisting
Air Flow Rates 60,000 cfm @ 12" w.c.
Fuel Consumption 11.03 Gallons per hour
Fuel Storage 200 gallons
Electrical System 12V dc
Weight 31,860 lbs. actual
Brakes Air
Paint ETI Gray
Warranty One Year or 1500 hours
Whichever occurs first limited

Options

Diesel Powered

Liquid Cooled Tier 3 225hp

Electric Powered

200 HP 480 VAC 3 PH

Filter

Standard Qx Media 80/20 Blend

SB (Spun Bonded Polyester) MERV 12 initial rating

SBTX (HEPA Equivalent)

Filter Restriction Warning Light

Pulse System

Onboard Air Compressor

Waste Removal

Gravity Dump

Electric Powered Auger

Hydraulic Powered Auger

Vibrator – Air Powered

Vibrator – Electric Powered

Frame Configuration

Skid With Gravity Dump

Skid With Auger Discharge

Trailer With Auger Discharge

Crane Pick Points

Fork Lift Pockets

Axles

Tandem Axle with 16K capacity air brakes

Hopper Configuration

Quick release inlet connectors and clamps

Storage Storage Boxes

Jack Heavy Duty Jack

Fuel Large Fuel Fill

Grease Gun

Tie Down Points

Dryer Air Dryer

Paint Custom Company Color